

BRITA® | PRO



SOFTENER PLUS CARBON FILTRATION

Hardness, Taste and Odor

Also available
in GOLD Series

Softens water, reduces Chlorine and improves Taste & Order

Easy-to-read and program valve head



CONTROL VALVE



PRESSURE TANK



NSF/ANSI STANDARDS

Tested and Certified by WQA against NSF/ANSI 44 for softening performance.



This control valve and pressure tank is Tested and Certified by NSF International against NSF/ANSI Standard 44 for material and structural integrity requirements.

COMPONENT







Upflow
Regeneration



- Metered downflow generation
- WQA Certified Components
- NSF Certified Components
- All materials certified to NSF/ANSI Standard 44
- Quick connect fittings (includes straight and elbow connectors)
- Reduces chlorine taste and odor

PLATINUM SERIES 1" UPFLOW SOFT+CTO

System Capacity Grains 18,750	System Capacity Grains 31,250	System Capacity Grains 37,500	System Capacity Grains 62,500
 Flow Rate @ 15 Service USGPM NA Backwash USGPM 2.0 Resin Type Aquafine™ 8% High Capacity Ion Exchange	 Flow Rate @ 15 Service USGPM NA Backwash USGPM 2.4 Resin Type Aquafine™ 8% High Capacity Ion Exchange	 Flow Rate @ 25 Service USGPM 16.6 Backwash USGPM 3.5 Resin Type Aquafine™ 8% High Capacity Ion Exchange	 Flow Rate @ 25 Service USGPM 17.0 Backwash USGPM 5.0 Resin Type Aquafine™ 8% High Capacity Ion Exchange
9 x 48	10 x 54	12 x 52 JACKET NOT AVAILABLE	14 x 65 JACKET NOT AVAILABLE

Not available in CA and WI.

The BRITA trademark and logo are registered trademarks of Brita LP and are used under license by Protect Plus, LLC. All rights reserved.