

BRITA® | PRO



SOFTENER PLUS IRON FILTRATION

Hardness, Iron, and Manganese

Also available
in GOLD Series

Easy-to-read and program valve head
Metered downflow generation
Softens water



CONTROL VALVE



PRESSURE TANK



NSF/ANSI STANDARDS
Tested and Certified by WQA against NSF/ANSI 44 for softening performance.







This control valve and pressure tank is Tested and Certified by NSF International against NSF/ANSI Standard 44 for material and structural integrity requirements.

COMPONENT

- Metered downflow generation
- WQA Certified Components
- NSF Certified Components
- All materials certified to NSF/ANSI Standard 44
- Quick connect fittings (includes straight and elbow connectors)
- Reduces hardness, iron, and manganese

PLATINUM SERIES 1" DOWNFLOW SOFT+IRON

System Capacity Grains 30,000	System Capacity Grains 45,000	System Capacity Grains 60,000	System Capacity Grains 90,000
			
Flow Rate @ 25 Service USGPM 15.8 Backwash USGPM 2.0	Flow Rate @ 25 Service USGPM 15.9 Backwash USGPM 2.4	Flow Rate @ 25 Service USGPM 17.1 Backwash USGPM 3.5	Flow Rate @ 25 Service USGPM 17.4 Backwash USGPM 5.0
Resin Type Purolite® SST-60	Resin Type Purolite® SST-60	Resin Type Purolite® SST-60	Resin Type Purolite® SST-60
9 x 48	10 x 54	12 x 52 JACKET NOT AVAILABLE	14 x 65 JACKET NOT AVAILABLE

Not available in CA and WI.

The BRITA trademark and logo are registered trademarks of Brita LP and are used under license by Protect Plus, LLC. All rights reserved.