

BRITA[®] | PRO



WATER SOFTENER

RELIABLE SOFTENING



- Easy to read and program valve head
- Metered downflow generation



CONTROL VALVE



PRESSURE TANK



NSF/ANSI STANDARDS

Tested and Certified by WQA against NSF/ANSI 44 for softening performance.







This control valve and pressure tank is Tested and Certified by NSF International against NSF/ANSI Standard 44 for material and structural integrity requirements.

COMPONENT

- WQA Certified Systems
- NSF Certified Components
- All materials certified to NSF/ANSI Standard 44
- Quick connect fittings (includes straight and elbow connectors)
- Up to four tank sizes available
- Softens water



SILVER SERIES 3/4" DOWNFLOW

System Capacity Grains 18,750	System Capacity Grains 25,000	System Capacity Grains 37,500	System Capacity Grains 50,000
<p>Flow Rate @ 25</p> <p>Service USGPM 14.3</p> <p>Backwash USGPM 1.5</p>  <p>8 x 44</p>	<p>Flow Rate @ 25</p> <p>Service USGPM 15.0</p> <p>Backwash USGPM 2.0</p>  <p>9 x 48</p>	<p>Flow Rate @ 25</p> <p>Service USGPM 15.1</p> <p>Backwash USGPM 2.4</p>  <p>10 x 54</p>	<p>Flow Rate @ 25</p> <p>Service USGPM 16.2</p> <p>Backwash USGPM 3.5</p>  <p>12 x 52 JACKET NOT AVAILABLE</p>

Not available in CA and WI.

The BRITA trademark and logo are registered trademarks of Brita LP and are used under license by Protect Plus, LLC. All rights reserved.